

TECHNICAL DATA SHEET

SVITOL EASY SPORT

- PRODUCT DESCRIPTION

High-performance, long-lasting lubricant. Perfect for lubricating moving parts. It lubricates effectively both in the fluid and solid phases. It contains molybdenum disulfide whose particles, highly micronized and in colloidal suspension, are absorbed by uneven surfaces, improving their finish. The special formulation ensures that the molybdenum disulfide attaches to the metal counter-wall, drastically reducing the friction and promoting the formation of a film of oil.

- **Lubricant:** using a cutting-edge technology, it reduces friction and specifically meets the need for lubrication that limits damage due to material fatigue.
- **Protective:** it joins to metals, preventing oxidation. Resistant to atmospheric agents.
- **Detergent:** it exerts a powerful cleansing action, it degreases and deep cleans reels, chains, cables, levers and disassembled parts. Perfect for removing oil, grease, tar, resin, carbon deposits and gunpowder.

- FIELDS OF USE

Suitable for all mechanical sports equipment that requires effective, long-lasting lubrication, such as: bicycles, fishing reels etc.

- TECHNICAL SPECIFICATIONS

•	Appearance	creamy
•	Color	straw-yellow
•	Odor	typical
•	Density at 15°C ASTM D1298	0.700 g/ml
•	Dropping Point (grease)	+ 250°C
•	NLGI gradation (grease)	2
•	Penetration (grease)	265 - 295
•	Operating temperature	$-40^{\circ}C + 170^{\circ}C$

- METHOD OF USE

Shake the bottle before use. Spray from a distance of approx. 20 cm. For precise dispensing, place the straw in the appropriate dispenser.

A special valve allows delivery even when the can is upside down.

- STORAGE

Unopened and stored at room temperature at least 3 years

- PACKAGING

Spray can

Code 2387	200 ml
Code 2393	50 ml

- NOTES

For information on product safety, please consult Safety Data Sheets.

TS 21.09.18

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO Via Antica di Cassano, 23 20063Cernusco sul Naviglio (MI) Italy Capitale Sociale: € 15.000.000,00 I.V. Registro delle Imprese di Milano n. 09728360968 Codice Fiscale e Partita IVA 09728360968 Direzione e coordinamento es art. 2497 c.c. PLI (Netherlands) B.V. Centralino 02 92436.1 Fax 02 92436.306 Www.arexons.com

A wholly-owned subsidiary of PETRONAS

Sistemi di gestione di qualità della società Arexons S.p.A. certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A. certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

