



EXPERIENCE TO PERFORM

## TECHNICAL DATA SHEET

# SVITOL EASY GREASE

### - **PRODUCT DESCRIPTION**

Grease formulated with a sophisticated saponification technology, based on white paraffin mineral oil and an "aluminum complex" mixed with PTFE and adhesive polymers.

This enables the product to have a low drip point, therefore, the degreaser:

- Lasts over time
- Maintains its properties unchanged over a broad temperature range
- Is resistant to atmospheric agents

The PTFE (polytetrafluoroethylene) additive reduces the friction coefficient and makes the product particularly useful in the critical start-up phase.

The special adhesive additives ensure a powerful grip to metal surfaces and so the maximum resistance to centrifugation and atmospheric agents.

It does not drip.

### - **FIELDS OF USE**

It ensures long-term lubrication of mechanical couplings, controls, transmission chains, agricultural machinery, garden equipment. Perfect for moving vertical surfaces.

Marked anti-wear and anti-seizure effect.

### - **TECHNICAL SPECIFICATIONS**

- |                              |              |
|------------------------------|--------------|
| • Appearance                 | creamy       |
| • Color                      | straw-yellow |
| • Odor                       | typical      |
| • Density at 15°C ASTM D1298 | 0.700 g/ml   |
| • Dropping Point (grease)    | + 250°C      |
| • NLGI gradation (grease)    | 2            |
| • Penetration (grease)       | 265 - 295    |
| • Operating temperature      | -40°C +170°C |

### - **METHOD OF USE**

Shake the bottle before use. Spray from a distance of approx. 20 cm. For precise dispensing, place the straw in the appropriate dispenser.

A special valve allows delivery even when the can is upside down.

### - **WARNINGS**

Do not use on live equipment, turn on power only after the complete evaporation of the solvent. Do not apply to overheated materials.

### - **STORAGE**

Unopened and stored at room temperature at least 3 years

### - **PACKAGING**

Spray can

Code 2391      200 ml

### - **NOTES**

For information on product safety, please consult Safety Data Sheet.

TS 21.09.18

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO  
Via Antica di Cassano, 23  
20063 Cernusco sul Naviglio (MI) Italy  
Capitale Sociale: € 15.000.000,00 I.V.  
Registro delle Imprese di Milano n. 09728360968  
Codice Fiscale e Partita IVA 09728360968  
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.  
Centralino 02 92436.1  
Fax 02 92436.306  
[www.arexons.com](http://www.arexons.com)

A wholly-owned subsidiary of PETRONAS

Sistemi di gestione di qualità della società Arexons S.p.A.  
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.  
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

arexons  
SINCE 1925