



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET



SVITOL *SPECIALTIES* OLIATORE

PRODUCT FEATURES

White oil for technical use, protects parts of minute mechanics from moisture and corrosion. It deeply lubricates even parts that are difficult to access. Avoid squeaking of moving parts.

APPLICATIONS

Ideal for sewing machines is able to lubricate and protect old typewriters, locks, weapons, calcs and all minute mechanisms

CLASSIFICATION

AREA OF USE

Suggested for household and technical maintenance. Lubricating of moving parts and pivot points on hinges, rolling chairs, suitcase wheels, chains.....
Lubricating of sewing machines, bikes.
Cleaning and protecting tools

ADDITIONAL INFO

Please check the compatibility in a hidden parts.

SHELF LIFE

At least 3 years if stored under the following conditions: in the original and sealed packaging, indoors and away from direct sunlight, over a temperature range between 5°C and 35°C.

PACKAGING

Cod. 9817 - 9816 PE bottle 90 ml

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.



A wholly-owned subsidiary of PETRONAS



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

CHEMICAL & PHYSICAL PROPERTIES

• Apperance	Liquid
• Color	Uncolored
• Density	0,847 g/ml
• Viscosity at 40°C	14 cSt
• Melting point	-15°C
• flash point (open cup)	>150°C
• total acid number	0,03 mg KOH/gr
• Solubility in water	Insoluble

ADDITIONAL INFO

For more information on product safety please consult Material Safety Data Sheets.

T.S. 24-03-2023

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user.
For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.



A wholly-owned subsidiary of PETRONAS